

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 01/30/2020

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Identifier

Product Name: Nitric Acid, Less than 70% HNO₃

Intended Use of the Product Not available

Name, Address, and Telephone of the Responsible Party

Company

LSB Chemical L.L.C. P.O. Box 2469 8490 West Bay Road Baytown, TX 77522 T (281) 383-5020 F (281) 383-7217

Emergency Telephone Number

Emergency number : (281) 383-5020, (800) 424-9300 (CHEMTREC, 24 hours)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification(GHS-US)Ox. Liq. 3H272Met. Corr. 1H290Skin Corr. 1AH314Eye Dam. 1H318

Label Elements

GHS-US Labeling Hazard Pictograms (GHS-US)



Signal Word (GHS-US)	: Danger
Hazard Statements (GHS-US)	: H272 - May intensify fire; oxidizer
	H290 - May be corrosive to metals
	H314 - Causes severe skin burns and eye damage
	H318 - Causes serious eye damage
Precautionary Statements (GHS-US)	: P210 - Keep away from heat, sparks, open flames, hot surfaces No smoking.
	P220 - Keep/Store away from extremely high or low temperatures, ignition sources, combustible materials, incompatible materials.
	P221 - Take any precaution to avoid mixing with incompatible materials, ignition sources, combustible materials.
	P234 - Keep only in original container.
	P260 - Do not breathe vapors, mist, spray.
	P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
	P280 - Wear protective gloves, protective clothing, eye protection, face protection, respiratory protection.
	P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated
	clothing. Rinse skin with water/shower.
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
	P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P310 - Immediately call a POISON CENTER or doctor.
	P321 - Specific treatment (see section 4).

Version: 2.2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use appropriate media for extinction.
P390 - Absorb spillage to prevent material damage.
P405 - Store locked up.
P406 - Store in corrosive resistant container with a resistant inner liner
P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. May cause or intensify fire; oxidizer.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Substances</u>

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Nitric acid	(CAS No) 7697-37-2	56 - 70	Ox. Liq. 3, H272
			Met. Corr. 1, H290
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
Water	(CAS No) 7732-18-5	30 - 44	Not classified

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call for medical assistance.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Immediately call for medical assistance. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call for medical assistance.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call for medical assistance.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

Inhalation: Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Skin Contact: Causes severe irritation which will progress to chemical burns.

Eye Contact: Causes serious eye damage.

Ingestion: Contact may cause immediate severe irritation progressing quickly to chemical burns. Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: May cause erosion of the teeth, or chronic bronchitis.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Special Hazards Arising From the Substance or Mixture

Fire Hazard: May intensify fire; oxidizer. Will burn if exposed to heat, and in addition, will accelerate the burning of other combustibles, resulting in more rapid spread of fire.

Explosion Hazard: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. **Reactivity:** Thermal decomposition generates : Corrosive vapors, toxic vapors. Can react explosively with reducing agents, metal powders, hydrogen sulfide, nitrate, and organic materials.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. **Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Nitrogen oxides, acrid vapors.

Other information: Do not allow run-off from fire fighting to enter drains or water courses. Use water spray to disperse vapors. **Reference to Other Sections**

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do NOT breathe (vapors, mist, spray). Avoid all contact with skin, eyes, or clothing. Keep away from

heat/sparks/open flames/hot surfaces. - No smoking.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Cautiously neutralize spilled liquid.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb spillage to prevent material damage. Cautiously neutralize spilled liquid. Contact competent authorities after a spill.

Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: May be corrosive to metals. When heated to decomposition, emits toxic fumes. Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do no eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Keep/Store away from extremely high or low temperatures, direct sunlight, heat, ignition sources, combustible materials, incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Finely divided metals. Hydrogen sulfide. Reducing agents. Combustible materials.

Specific End Use(s) Not available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitric acid (7697-37-2)		
Mexico	OEL TWA (mg/m³)	5 mg/m ³
Mexico	OEL TWA (ppm)	2 ppm
Mexico	OEL STEL (mg/m³)	10 mg/m ³
Mexico	OEL STEL (ppm)	4 ppm
USA ACGIH	ACGIH TWA (ppm)	2 ppm
USA ACGIH	ACGIH STEL (ppm)	4 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	2 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	2 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	4 ppm
USA IDLH	US IDLH (ppm)	25 ppm
Alberta	OEL STEL (mg/m³)	10 mg/m ³
Alberta	OEL STEL (ppm)	4 ppm
Alberta	OEL TWA (mg/m³)	5.2 mg/m ³
Alberta	OEL TWA (ppm)	2 ppm
British Columbia	OEL STEL (ppm)	4 ppm
British Columbia	OEL TWA (ppm)	2 ppm
Manitoba	OEL STEL (ppm)	4 ppm
Manitoba	OEL TWA (ppm)	2 ppm
New Brunswick	OEL STEL (mg/m³)	10 mg/m ³
New Brunswick	OEL STEL (ppm)	4 ppm
New Brunswick	OEL TWA (mg/m³)	5.2 mg/m ³
New Brunswick	OEL TWA (ppm)	2 ppm
Newfoundland & Labrador	OEL STEL (ppm)	4 ppm
Newfoundland & Labrador	OEL TWA (ppm)	2 ppm
Nova Scotia	OEL STEL (ppm)	4 ppm
Nova Scotia	OEL TWA (ppm)	2 ppm
Nunavut	OEL STEL (mg/m ³)	10 mg/m ³
Nunavut	OEL STEL (ppm)	4 ppm
Nunavut	OEL TWA (mg/m³)	5.2 mg/m ³
Nunavut	OEL TWA (ppm)	2 ppm
Northwest Territories	OEL STEL (mg/m³)	10 mg/m ³
Northwest Territories	OEL STEL (ppm)	4 ppm
Northwest Territories	OEL TWA (mg/m³)	5.2 mg/m ³
Northwest Territories	OEL TWA (ppm)	2 ppm
Ontario	OEL STEL (ppm)	4 ppm
Ontario	OEL TWA (ppm)	2 ppm
Prince Edward Island	OEL STEL (ppm)	4 ppm
Prince Edward Island	OEL TWA (ppm)	2 ppm
Québec	VECD (mg/m ³)	10 mg/m ³
Québec	VECD (ppm)	4 ppm
Québec	VEMP (mg/m ³)	5.2 mg/m ³
Québec	VEMP (ppm)	2 ppm
Saskatchewan	OEL STEL (ppm)	4 ppm
Saskatchewan	OEL TWA (ppm)	2 ppm
Yukon	OEL STEL (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (ppm)	4 ppm

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Yukon	OEL TWA (mg/m³)	5 mg/m ³
Yukon	OEL TWA (ppm)	2 ppm

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use explosion-proof equipment. Ensure all national/local regulations are observed. Alarm detectors should be used when toxic gases may be released.

Personal Protective Equipment: Gloves. Respiratory protection of the dependent type. Protective goggles. Protective clothing.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosion-proof clothing. Wear fire/flame resistant/retardant clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

information on basic ringsical and chemical rioper	ue:	<u>2</u>
Physical State	:	Liquid
Appearance	:	Colorless, light brown
Odor	:	Acrid
Odor Threshold	:	Not available
рН	:	<1
Relative Evaporation Rate (butylacetate=1)	:	~1
Melting Point	:	Not available
Freezing Point	:	(56.5% HNO ₃ = -20°F); (65.0% HNO ₃ = -28°F); (66.0% HNO ₃ = -32°F)
Boiling Point	:	(56.5% HNO ₃ = 243°F); (65.0% HNO ₃ = 246°F); (66.0% HNO ₃ = 248°F)
Flash Point	:	Not available
Degrees Baume	:	(56.5% HNO ₃ = 38); (65.0% HNO ₃ = 40); (66.0% HNO ₃ = 41)
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	9 - 10 mm Hg @25°C (77°F)
Relative Vapor Density at 20 °C	:	> 1 (air=1)
Relative Density	:	Not available
Specific Gravity	:	(56.5% HNO ₃ = 1.3551); (65.0% HNO ₃ = 1.3841); (66.0% HNO ₃ = 1.3887) @25°C (77°F)
Solubility	:	Miscible.
Viscosity	:	(56.5% HNO ₃ = 2.0cp); (65.0% HNO ₃ = 2.1cp); (66.0% HNO ₃ = 2.2cp) @20°C (68°F)
Explosion Data – Sensitivity to Mechanical Impact	:	Not available
Explosion Data – Sensitivity to Static Discharge	:	Not available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates : Corrosive vapors. Can react explosively with reducing agents, metal powders, hydrogen sulfide, nitrate, and organic materials.

Chemical Stability: May intensify fire; oxidizer.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Overheating. Open flame. Incompatible materials. Adding water to acid should be avoided.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Metals. May be corrosive to metals. Reducing agents. Amines.

Hazardous Decomposition Products: Thermal decomposition generates : Corrosive vapors. Nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity : Not classified.

LD50 and LC50 Data Not available

Skin Corrosion/Irritation: Causes severe skin burns and eye damage. pH: <1

Serious Eye Damage/Irritation: Causes serious eye damage. pH: <1

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Skin Contact: Causes severe irritation which will progress to chemical burns.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Contact may cause immediate severe irritation progressing quickly to chemical burns. Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: May cause erosion of the teeth, or chronic bronchitis.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data

Water (7732-18-5)	
LD50 Oral Rat	> 90000 mg/kg
Nitric acid (7697-37-2)	
LC50 Inhalation Rat (mg/l)	0.13 mg/l (Exposure time: 4 h)
LC50 Inhalation Rat (ppm)	67 ppm/4h

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified

Persistence	and Degradabilit	Y

Not established.	
Not established.	
-2.3 (at 25 °C)	
	Not established.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 1/1. TRANSPORT INFORMATION

SECTION 14: TRANSPORT	INFORMATION
14.1 In Accordance with DO	г
Proper Shipping Name	: NITRIC ACID other than red fuming with at least 65%, but not more than 70% nitric acid
Hazard Class	: 8
Identification Number	: UN2031
Label Codes	: 8,5.1
Packing Group	: 11
ERG Number	: 157
14.2 In Accordance with IMI	DG
Proper Shipping Name	: NITRIC ACID other than red fuming with at least 65%, but not more than 70% nitric acid
Hazard Class	: 8
Identification Number	: UN2031
Packing Group	: II
Label Codes	: 8,5.1
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-Q
14.3 In Accordance with IAT	Α
Proper Shipping Name	: NITRIC ACID other than red fuming with at least 65%, but not more than 70% nitric acid
Packing Group	: 11
Identification Number	: UN2031
Hazard Class	: 8
Label Codes	: 8,5.1
ERG Code (IATA)	: 8L
14.4 In Accordance with TD	i de la constante de
Proper Shipping Name	: NITRIC ACID other than red fuming with not more than 70 per cent nitric acid
Packing Group	: II
Hazard Class	: 8
Identification Number	: UN2031
Label Codes	: 8
SECTION 15: REGULATOR	(INFORMATION
US Federal Regulations	
Nitric Acid, Less than 70% HNC	3
SARA Section 311/312 Hazard	Classes Immediate (acute) health hazard
	Reactive hazard
Water (7732-18-5)	
Listed on the United States TSC	A (Toxic Substances Control Act) inventory

Nitric acid (7697-37-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 302 (Specific toxic chemical listings)

SADA Soctio - 212 /C -: 6: - + -مام مان Listad

Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 302 Threshold Planning Quantity (TPQ)	1000
SARA Section 313 - Emission Reporting	1.0 %

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

US State Regulations

-		-	
Nitric	acid	(7697-3	37-21

Nitric acid (7697-37-2)
U.S California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S California - SCAQMD - Toxic Air Contaminants With Proposed Risk Values
U.S California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S Delaware - Accidental Release Prevention Regulations - Sufficient Quantities
U.S Delaware - Accidental Release Prevention Regulations - Threshold Quantities
U.S Delaware - Accidental Release Prevention Regulations - Toxic Endpoints
U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S Idaho - Occupational Exposure Limits - TWAs
U.S Illinois - Toxic Air Contaminants
U.S Louisiana - Reportable Quantity List for Pollutants
U.S Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S Massachusetts - Right To Know List
U.S Massachusetts - Toxics Use Reduction Act
U.S Michigan - Occupational Exposure Limits - STELs
U.S Michigan - Occupational Exposure Limits - TWAs
U.S Michigan - Polluting Materials List
U.S Michigan - Process Safety Management Highly Hazardous Chemicals
U.S Minnesota - Chemicals of High Concern
U.S Minnesota - Hazardous Substance List
U.S Minnesota - Permissible Exposure Limits - STELs
U.S Minnesota - Permissible Exposure Limits - TWAs
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S New Jersey - Discharge Prevention - List of Hazardous Substances
U.S New Jersey - Environmental Hazardous Substances List
U.S New Jersey - Right to Know Hazardous Substance List
U.S New Jersey - Special Health Hazards Substances List
U.S New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S New York - Occupational Exposure Limits - TWAs
U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S North Carolina - Control of Toxic Air Pollutants
U.S North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S Ohio - Accidental Release Prevention - Threshold Quantities
U.S Ohio - Extremely Hazardous Substances - Threshold Quantities
U.S Oregon - Permissible Exposure Limits - TWAs
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S Pennsylvania - RTK (Right to Know) List
U.S Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S Tennessee - Occupational Exposure Limits - STELs

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Tennessee - Occupational Exposure Limits - TWAs

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits STELs
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet
- U.S. Wyoming Process Safety Management Highly Hazardous Chemicals

Canadian Regulations

Nitric Acid, Less than 70% HNO ₃		
WHMIS Classification	Class E - Corrosive Material	
	Class C - Oxidizing Material	
Water (7732-18-5)		
Listed on the Canadian DSL (Domestic Substances List) inventory.		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Nitric acid (7697-37-2)		
Listed on the Canadian DSL (Domestic Substances List) inventory.		
Listed on the Canadian Ingredient Disclosure List		
WHMIS Classification	Class C - Oxidizing Material	
	Class E - Corrosive Material	
This product has been class	sified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION Revision date : 01/30/2020

Revision date	: 01/30/2020
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA
	Hazard Communication Standard 29 CFR 1910.1200.
GHS Full Text Phrases:	

Eye Dam. 1	Serious eye damage/eye irritation Category 1
Met. Corr. 1	Corrosive to metals Category 1
Ox. Liq. 3	Oxidizing liquids Category 3
Skin Corr. 1A	Skin corrosion/irritation Category 1A
H272	May intensify fire; oxidizer
H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA Health Hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA Fire Hazard	: 0 - Materials that will not burn.
NFPA Reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
NFPA Specific Hazard	: OX - This denotes an oxidizer, a chemical which can greatly increase the rate of combustion/fire.
Party Responsible for the Prep	paration of This Document
LSB Chemical L.L.C.	
8490 West Bay Road	
P.O. Box 2469	
Baytown, TX 77522	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS

T: (281) 383-5020